

M280 WD - PROFESSIONAL
WET & DRY



FOOD INDUSTRY



BUILDING AND CONSTRUCTION



WINE



COFFEE, TEA, TOBACCO PROCESSING



SUCTION UNIT

Power	kW	2,3
Max water lift	mmH ₂ O	2500
Max air flow	m ³ /h	360
Suction inlet	mm	80
Noise level (EN ISO 3744)	dB(A)	76

FILTER UNIT

Filter Type	Bag
Media - Filtration	Polypropilene - 300µm

COLLECTION UNIT

Discharge system	
Capacity	l 80

VOLUME

Dimensions	cm	53x59x106h
Weight	kg	40

- ✓ Two powerful by pass motors with independent cooling
- ✓ Compact and mobile
- ✓ Discharge hose for liquids
- ✓ Accessory kit as standard
- ✓ Double stage filtration for liquids (PPL + foam filter)
- ✓ Ideal for suction of great quantities of liquids

SUCTION UNIT

The suction is provided by two by-pass motors, using carbon brushes, operated by independent switches and placed inside a sturdy steel casing, filled with soundproofing material.

FILTER UNIT

A floating device stops the suction whenever the liquid in the container reaches the maximum level and prevents overflowing.
The polyester bag filter, placed inside the filtering chamber, guarantees a wide filtering surface and high resistance to dust passage and clogging.

COLLECTION UNIT

The vacuum cleaner is mounted on a solid steel trolley, provided with a support for hoses when not used, and equipped with oil proof wheels and braking castors.
The suctioned liquid can be discharged by using a discharge pipe located at the back of the liquid vacuum cleaner

OPTIONALS

- ✓ OTHER VOLTAGES AND FREQUENCIES AVAILABLE UPON REQUEST