

MDF Frame HEPA Filter - H10, H13 & H14



Media	Microglass Fiber
Frame	MDF
Final Pressure Drop	600 Pa
Operating Temperature	80°C
Filter Efficiency****	E10-H14
Gasket	Flat Neoprene or Half Round Endless Polyurethane
Protection Grids	Optional
Separators	Hotmelt

Applications

- Air conditioning systems (Hospitals, Laboratories, Museums)
- Industrial processes (Pharmaceutical, Food, Microelectronics)

Part Number	Filter Class EN 1822	Dimensions			Media Area (m2)	Air Flow (m3/hr)	Pressure Drop (Pa)
		Width (mm)	Length (mm)	Depth (mm)			
HFH-305/305/292-10PD	H10	305	305	292	5.6	1050	250
HFH-305/610/292-10PD	H10	305	610	292	11.2	2100	250
HFH-457/457/292-10PD	H10	457	457	292	12.6	2360	250
HFH-457/610/292-10PD	H10	457	610	292	16.8	3150	250
HFH-610/610/292-10PD	H10	610	610	292	22.4	4200	250
HFH-305/305/292-13PD	H13	305	305	292	5.6	600	250
HFH-305/610/292-13PD	H13	305	610	292	11.2	1200	250
HFH-457/457/292-13PD	H13	457	457	292	12.6	1347	250
HFH-457/610/292-13PD	H13	457	610	292	16.8	1798	250
HFH-610/610/292-13PD	H13	610	610	292	22.4	2400	250
HFH-305/305/292-14PD	H14	305	305	292	5.6	538	250
HFH-305/610/292-14PD	H14	305	610	292	11.2	1075	250
HFH-457/457/292-14PD	H14	457	457	292	12.6	1207	250
HFH-457/610/292-14PD	H14	457	610	292	16.8	1610	250
HFH-610/610/292-14PD	H14	610	610	292	22.4	2150	250