



DUST SPARES
dust control spare parts for industry
www.dustspares.co.uk 03456 800 696

MW Fine Filter - M6, F7, F8 & F9 Grade



Media	Microglass Fiber
Frame	PS
Final Pressure Drop	450 Pa
Operating Temperature	80°C
Filter Efficiency*	M6-F7-F8-F9
Filter Class**	ISO ePM10 / ISO ePM1
Gasket	Optional
Sealant	Polyurethane
Separators	Hot Melt
Header Thickness	20 mm, 25 mm

Applications

- HVAC

Advantages

- Compact and economic
- High surface area
- High efficiency

Part Number	EN 779:2012 Efficiency	ISO 16890 Class	Dimensions			Media Area (m ²)	Air Flow (m ³ /h)	Pressure Drop (Pa)	Energy (***)
			Length (mm)	Width (mm)	Depth (mm)				
MW-F6-01	M6	ISO ePM10 65%	292	592	292	4,50	1750	80	E
MW-F6-02	M6	ISO ePM10 65%	492	592	292	7,50	2800	80	E
MW-F6-03	M6	ISO ePM10 65%	592	592	292	9,00	3400	80	E
MW-F7-01	F7	ISO ePM1 50%	292	592	292	4,50	1750	115	D
MW-F7-02	F7	ISO ePM1 50%	492	592	292	7,50	2800	115	D
MW-F7-03	F7	ISO ePM1 50%	592	592	292	9,00	3400	115	D
MW-F8-01	F8	ISO ePM1 60%	292	592	292	4,50	1750	120	D
MW-F8-02	F8	ISO ePM1 60%	492	592	292	7,50	2800	120	D
MW-F8-03	F8	ISO ePM1 60%	592	592	292	9,00	3400	120	D
MW-F9-01	F9	ISO ePM1 75%	292	592	292	4,50	1750	150	E
MW-F9-02	F9	ISO ePM1 75%	492	592	292	7,50	2800	150	E
MW-F9-03	F9	ISO ePM1 75%	592	592	292	9,00	3400	150	E

* According to EN 779:2012

**According to ISO 16890

***According to Eurovent 4/21-2019

