



M 150 WD - PROFESSIONAL WET & DRY



FOOD INDUSTRY




WINE



CLEANING CONTRACTORS



VEHICLE - TRANSPORT CLEANING



- ✓ Complete steel construction
- ✓ Compact and mobile
- ✓ Easy filter replacement

- ✓ Floating device to stop the suction when container is full
- ✓ Discharge hose for liquids
- ✓ Accessory kit as standard



SUCTION UNIT

Voltage	V - Hz	230 - 50 1~
Power	kW	1,15
Max waterlift	mmH2O	2.500
Max air flow	m³/h	180
Suction inlet	mm	50
Noise level (EN ISO 3744)	dB(A)	74



FILTER UNIT

Filter Type	Star	
Material - Efficiency	IEC 60335-2-69	Kit wet + Kit dry



COLLECTION UNIT

Discharge system	Discharge hose	
Capacity	lt.	50



VOLUME

Dimensions	cm	52x40x90h
Weight	kg	28



SUCTION UNIT

The suction is made by a carbon brush by-pass motor which is activated by an independent switch placed inside a robust metal motor head. The motor head is soundproofed by sound-absorbent material.



FILTER UNIT

A floating device stops the suction whenever the liquid in the container reaches the maximum level and prevents overflowing.

A propylene filter for liquids is installed upstream. This filter guarantees the efficient filtration of the vacuumed oil; an additional plastic foam filter prevents most of the liquid mist from getting to the motor.



COLLECTION UNIT

The vacuum is assembled onto a sturdy steel chassis, and provided with industrial quality wheels , that make it suitable for mobile service even when used on rough surfaces.



OPTIONALS

- ✓ OTHER VOLTAGES AND FREQUENCIES AVAILABLE UPON REQUEST
- ✓ STAINLESS STEEL COLLECTION TANK